

SENSE

FILE NO

RT20k_S1

RESISTANCE

R25 = 20kOhm \pm 1%

B VALUE

B25/50 = 3950K \pm 1%

Temp. (deg. C)	Min R (kohm)	Nomal R (kohm)	Max R (kohm)	Temp. (deg. C)	Min R (kohm)	Nomal R (kohm)	Max R (kohm)
-40	648,740	678,800	710,180	-8	97,246	99,820	102,450
-39	607,460	635,180	664,110	-7	92,210	94,600	97,042
-38	569,070	594,650	621,320	-6	87,464	89,683	91,949
-37	533,350	556,960	581,560	-5	82,989	85,050	87,153
-36	500,100	521,900	544,590	-4	78,770	80,684	82,635
-35	469,130	489,260	510,210	-3	74,790	76,567	78,378
-34	440,270	458,870	478,210	-2	71,035	72,684	74,364
-33	413,370	430,560	448,420	-1	67,489	69,020	70,579
-32	388,280	404,170	420,670	0	64,141	65,563	67,009
-31	364,870	379,570	394,810	1	60,981	62,301	63,643
-30	343,020	356,610	370,700	2	57,994	59,219	60,464
-29	322,620	335,200	348,230	3	55,170	56,307	57,462
-28	303,560	315,200	327,250	4	52,498	53,553	54,624
-27	285,740	296,520	307,670	5	49,971	50,950	51,943
-26	269,080	279,060	289,370	6	47,568	48,476	49,396
-25	253,490	262,730	272,280	7	45,294	46,136	46,988
-24	238,890	247,450	256,290	8	43,143	43,923	44,713
-23	225,230	233,160	241,350	9	41,107	41,830	42,561
-22	212,430	219,780	227,360	10	39,179	39,848	40,525
-21	200,430	207,240	214,270	11	37,352	37,972	38,598
-20	189,180	195,500	202,010	12	35,621	36,195	36,775
-19	178,620	184,480	190,510	13	33,981	34,512	35,047
-18	168,710	174,150	179,730	14	32,425	32,916	33,412
-17	159,410	164,450	169,630	15	30,950	31,404	31,861
-16	150,680	155,360	160,160	16	29,561	29,980	30,403
-15	142,480	146,820	151,270	17	28,242	28,630	29,020
-14	134,770	138,800	142,930	18	26,989	27,347	27,708
-13	127,530	131,260	135,090	19	25,800	26,130	26,462
-12	120,710	124,180	127,730	20	24,670	24,974	25,280
-11	114,300	117,520	120,820	21	23,595	23,876	24,157
-10	108,270	111,260	114,310	22	22,574	22,832	23,091
-9	102,590	105,370	108,200	23	21,603	21,840	22,078

SENSE

FILE NO

RT20k_S1

RESISTANCE

R25 = 20kOhm \pm 1%

B VALUE

B25/50 = 3950K \pm 1%

Temp. (deg. C)	Min R (kohm)	Nomal R (kohm)	Max R (kohm)	Temp. (deg. C)	Min R (kohm)	Nomal R (kohm)	Max R (kohm)
24	20,679	20,897	21,115	56	5,581	5,708	5,838
25	19,800	20,000	20,200	57	5,375	5,500	5,627
26	18,943	19,142	19,342	58	5,179	5,301	5,426
27	18,127	18,326	18,525	59	4,991	5,110	5,232
28	17,350	17,549	17,747	60	4,810	4,927	5,047
29	16,611	16,808	17,006	61	4,637	4,752	4,869
30	15,907	16,103	16,299	62	4,471	4,583	4,698
31	15,237	15,431	15,625	63	4,312	4,421	4,533
32	14,598	14,790	14,983	64	4,159	4,266	4,376
33	13,989	14,179	14,370	65	4,012	4,117	4,225
34	13,409	13,597	13,786	66	3,871	3,974	4,079
35	12,856	13,041	13,228	67	3,736	3,837	3,940
36	12,328	12,511	12,696	68	3,607	3,705	3,806
37	11,825	12,005	12,188	69	3,482	3,578	3,677
38	11,345	11,523	11,702	70	3,362	3,456	3,553
39	10,886	11,062	11,239	71	3,247	3,339	3,434
40	10,449	10,622	10,796	72	3,137	3,227	3,319
41	10,031	10,201	10,373	73	3,031	3,119	3,209
42	9,633	9,799	9,968	74	2,929	3,015	3,103
43	9,252	9,416	9,582	75	2,831	2,915	3,002
44	8,888	9,049	9,212	76	2,737	2,819	2,904
45	8,540	8,698	8,858	77	2,646	2,726	2,809
46	8,207	8,363	8,520	78	2,559	2,637	2,718
47	7,889	8,042	8,197	79	2,475	2,552	2,631
48	7,585	7,735	7,887	80	2,394	2,469	2,547
49	7,294	7,441	7,590	81	2,316	2,390	2,466
50	7,016	7,160	7,306	82	2,241	2,313	2,387
51	6,750	6,891	7,035	83	2,169	2,240	2,312
52	6,495	6,634	6,774	84	2,100	2,169	2,240
53	6,251	6,387	6,525	85	2,033	2,100	2,170
54	6,018	6,151	6,286	86	1,968	2,034	2,102
55	5,795	5,925	6,057	87	1,906	1,971	2,037

SENSE

FILE NO

RT20k_S1

RESISTANCE

R25 = 20kOhm \pm 1%

B VALUE

B25/50 = 3950K \pm 1%

Temp. (deg. C)	Min R (kohm)	Nomal R (kohm)	Max R (kohm)	Temp. (deg. C)	Min R (kohm)	Nomal R (kohm)	Max R (kohm)
88	1,846	1,909	1,974	110	0,952	0,991	1,031
89	1,789	1,850	1,914	111	0,925	0,963	1,003
90	1,733	1,793	1,856	112	0,899	0,936	0,975
91	1,680	1,738	1,799	113	0,874	0,911	0,949
92	1,628	1,685	1,745	114	0,850	0,886	0,923
93	1,578	1,634	1,693	115	0,826	0,862	0,898
94	1,530	1,585	1,642	116	0,804	0,838	0,874
95	1,483	1,537	1,593	117	0,782	0,815	0,850
96	1,439	1,491	1,546	118	0,761	0,794	0,828
97	1,395	1,447	1,500	119	0,740	0,772	0,806
98	1,354	1,404	1,456	120	0,720	0,752	0,785
99	1,313	1,363	1,414	121	0,701	0,732	0,764
100	1,275	1,323	1,373	122	0,682	0,712	0,744
101	1,237	1,284	1,333	123	0,664	0,694	0,725
102	1,201	1,247	1,295	124	0,646	0,676	0,706
103	1,166	1,211	1,258	125	0,629	0,658	0,688
104	1,132	1,176	1,222	126	0,613	0,641	0,670
105	1,099	1,143	1,188	127	0,597	0,624	0,653
106	1,068	1,110	1,154	128	0,581	0,608	0,636
107	1,037	1,079	1,122	129	0,566	0,593	0,620
108	1,008	1,048	1,091	130	0,552	0,577	0,604
109	0,979	1,019	1,060				